

Entropy – General Idea

Definition:

“In order to define information gain precisely, we begin by defining a measure commonly used in information theory, called entropy that characterizes the (im)purity of an arbitrary collection of examples”

Given a set of examples, S . And a binary categorisation

Where p_+ is the proportion of positive “examples”

And p_- is the proportion of negatives

$$Entropy(S) = -p_+ \log_2(p_+) - p_- \log_2(p_-)$$

Entropy – General Idea

➤ Entropy as a measure of Information

Ex. The information content of a message telling the outcome of flipping an honest coin is

$$\begin{aligned} I(\text{Coin Toss}) &= -p(\text{heads}) \log_2 p(\text{heads}) - p(\text{tails}) \log_2 p(\text{tails}) \\ &= -1/2 \log_2(1/2) - 1/2 \log_2(1/2) \\ &= 1 \text{ bit} \end{aligned}$$

If the coin has been rigged to come up heads 75% of the time, the information content will be less or more ?!

Entropy – General Idea

➤ Entropy as a measure of Information

Ex. The information content of a message telling the outcome of flipping an honest coin is

$$\begin{aligned} I(\text{Coin Toss}) &= -p(\text{heads}) \log_2 p(\text{heads}) - p(\text{tails}) \log_2 p(\text{tails}) \\ &= -1/2 \log_2(1/2) - 1/2 \log_2(1/2) \\ &= 1 \text{ bit} \end{aligned}$$

If the coin has been rigged to come up heads 75% of the time, the information content will be less or more ?!

$$\begin{aligned} I[\text{Coin Toss}] &= -3/4 \log_2(3/4) - 1/4 \log_2(1/4) \\ &= 0.811 \text{ bits} \end{aligned}$$

Remark: Note for users of old calculators:

May need to use the fact that $\log_2(x) = \ln(x)/\ln(2)$

And also note that, by convention: $0 \cdot \log_2(0)$ is taken to be 0

Entropy – General Idea

- In categorisations c_1 to c_n

Where p_n is the proportion of examples in c_n

$$Entropy(S) = -\sum_{i=1}^n p_i \log_2(p_i)$$


p_i is the probability of class i

Computes the entropy as the proportion of class i in the set.

The higher the entropy the more the information content.

Entropy – General Idea

Entropy




- S is a sample of training examples


Entropy(S)
positives p_+ approaches 0.5 (very impure),
the Entropy of S converges to 1.0

Entropy – General Idea Impurity


Very impure group



Less impure




**Minimum
impurity**



Entropy – General Idea Impurity

- What is the entropy of a group in which all examples belong to the same class?
 - entropy = $-1 \log_2 1 = 0$
 - **not a good training set for learning**

**Minimum
impurity**




7


Entropy – General Idea Impurity

- What is the entropy of a group in which all examples belong to the same class?
 - entropy = $-1 \log_2 1 = 0$
 - **not a good training set for learning**
- What is the entropy of a group with 50% in either class?
 - entropy = $-0.5 \log_2 0.5 - 0.5 \log_2 0.5 = 1$
 - good training set for learning**

**Minimum
impurity**



**Maximum
impurity**



8

Information Gain

We want to determine which **attribute** in a given set of training feature vectors is **most useful** for discriminating between the classes to be learned.

i.e.

Information gain tells us how **important** a given attribute of the feature vectors is.

We will use it to decide the order of attributes in the nodes of a decision tree.


9

Calculating Information Gain


Entire population (30 instances)

Find its entropy

$$-\left(\frac{14}{30} \cdot \log_2 \frac{14}{30}\right) - \left(\frac{16}{30} \cdot \log_2 \frac{16}{30}\right) = 0.996$$




$$-\left(\frac{13}{17} \cdot \log_2 \frac{13}{17}\right) - \left(\frac{4}{17} \cdot \log_2 \frac{4}{17}\right) = 0.787$$



Find its entropy
17 instances

$$-\left(\frac{1}{13} \cdot \log_2 \frac{1}{13}\right) - \left(\frac{12}{13} \cdot \log_2 \frac{12}{13}\right) = 0.391$$



Find its entropy
13 instances

$$\text{(Weighted) Average Entropy of Children} = \left(\frac{17}{30} \cdot 0.787\right) + \left(\frac{13}{30} \cdot 0.391\right) = 0.615$$

$$\text{Information Gain} = 0.996 - 0.615 = 0.38$$

10

Credit Risk Example

Let us consider our credit risk data. There are three feature values in 14 classes.

6 classes have high risk, 3 have moderate risk, 5 have low risk. Assuming *uniform* distribution, their probabilities are as follows:

NO.	RISK	CREDIT HISTORY	DEBT	COLLATERAL	INCOME
1.	high	bad	high	none	\$0 to \$15k
2.	high	unknown	high	none	\$15 to \$35k
3.	moderate	unknown	low	none	\$15 to \$35k
4.	high	unknown	low	none	\$0 to \$15k
5.	low	unknown	low	none	over \$35k
6.	low	unknown	low	adequate	over \$35k
7.	high	bad	low	none	\$0 to \$15k
8.	moderate	bad	low	adequate	over \$35k
9.	low	good	low	none	over \$35k
10.	low	good	high	adequate	over \$35k
11.	high	good	high	none	\$0 to \$15k
12.	moderate	good	high	none	\$15 to \$35k
13.	low	good	high	none	over \$35k
14.	high	bad	high	none	\$15 to \$35k

high $\frac{6}{14}$, moderate $\frac{3}{14}$, low $\frac{5}{14}$

Information contained in this partition:

$$\begin{aligned} \text{Info}(S) &= -(6/14) \log_2 (6/14) - \\ &\quad (3/14) \log_2 (3/14) - (5/14) \log_2 (5/14) \\ &\approx 1.531 \text{ bits} \end{aligned}$$

Expected Info.

Let property A(Income) be at the root, and let C_1, \dots, C_n be the partitions of the examples on this feature.

Information needed to build a tree for partition C_i is $I(C_i)$.

Expected information needed to build the whole tree is a *weighted average* of $I(C_i)$.

Let $|S|$ be the cardinality of set S .

Let $\{C_i\}$ be the set of all partitions.

Expected information needed to complete the tree with root A

$$\text{Info}_A(S) = \sum_{i=1}^n \frac{|C_i|}{|S|} \times I(C_i)$$

Expected Info.

In our data, there are three partitions based on income:

All examples have high risk:

$$I(C_1) = -1 \log_2 1 = 0.0.$$

$$C_1 = \{1, 4, 7, 11\}, |C_1| = 4, I(C_1) = 0.0$$

Two examples have high risk, two have moderate:

$$I(C_2) = -1/2 \log_2 1/2 - 1/2 \log_2 1/2 = 1.0.$$

$$C_2 = \{2, 3, 12, 14\}, |C_2| = 4, I(C_2) = 1.0$$

$$I(C_3) = -1/6 \log_2 1/6 - 5/6 \log_2 5/6 \approx 0.65.$$

$$C_3 = \{5, 6, 8, 9, 10, 13\}, |C_3| = 6, I(C_3) \approx 0.65$$

The expected information to complete the tree using income as the root feature is this:

$$4/14 * 0.0 + 4/14 * 1.0 + 6/14 * 0.65 \approx 0.564 \text{ bits}$$

$$\text{i.e. } Info_A(S) = 0.564$$

The gain of a property A

Now the information gain from selecting feature P for tree-building, given a set of classes C.

$$Gain(A) = Info(S) - Info_A(S)$$

For our sample data and for P = income, we get

$$Gain(A) = 1.531 - 0.564 \text{ bits} = 0.967 \text{ bits.}$$

The gain of a property A

Our analysis will be complete, and our choice clear, after we have similarly considered the remaining three features. The values are as follows:

Gain(COLLATERAL) ≈ 0.756 bits,

Gain(DEBT) ≈ 0.581 bits,

Gain(CREDIT HISTORY) ≈ 0.266 bits.

That is, we should choose INCOME as the criterion in the root of the best decision tree that we can construct. And continue recursively...

Recursively Creating the Decision Tree

